

ANSUL-A Municipal Class A Fire Control Concentrate 30 °F (-1.1 °C) to 120 °F (49 °C)

Description

ANSUL-A Municipal "Class A" Fire Control Concentrate is formulated using fluorine-free hydrocarbon surfactants to perform on Class A combustible materials typical in municipal applications. The ANSUL-A concentrate is designed for use between 0.1% and 1.0% in standard proportioning equipment.

TYPICAL PHYSICOCHEMICAL PROPERTIES AT 77 °F (25 °C)

Appearance	Clear Light Yellow Liquid
Density	1.01 g/ml ± 0.01
pH	7.0 – 8.5
Refractive Index	1.3486 ± 0.0025
Viscosity @25 °C	1.7 ± 0.5 cSt
Slush Point	28 °F (-2.2 °C)
Surface Tension	
	0.1% ANSUL-A solution 39.5 ± 0.8 dynes/cm
	0.6% ANSUL-A solution 30.2 ± 0.8 dynes/cm
	1.0% ANSUL-A solution 28.9 ± 0.8 dynes/cm

Application

ANSUL-A Municipal "Class A" Fire Control Concentrate is intended for use on Class A combustible fires. Its low surface tension demonstrates the excellent wetting characteristics needed to efficiently combat Class A fires. The ANSUL-A concentrate is not suitable for use on any fuel with an appreciable water solubility (polar solvents) such as methyl and ethyl alcohol, acetone, and methyl ethyl ketone; it is not intended for use on Class B hydrocarbons. This Compressed Air Foam System (CAFS) compatible concentrate can be used with both aspirating and non-aspirating discharge devices because of the low energy required to make it foam. ANSUL-A concentrate can also be used with dry chemical extinguishing agents without any regard to the order of application.

Performance

As with most conventional foam making equipment, the expansion of ANSUL-A Municipal "Class A" Fire Control Concentrate will vary depending on the performance characteristics of the equipment and the type of water (i.e., fresh, salt, or hard) at the correct dilution. Aspirating discharge devices produce expansion ratios from 6:1 to 10:1 depending primarily on the type of aspirating device and flow rate. In general, the higher the flow rate, the higher the expansion ratio. Non-aspirating devices such as hand line water fog/stream nozzles will give expansion ratios of 2:1 to 4:1.



007178

ANSUL-A concentrate can be proportioned easily at the correct dilution using most conventional equipment such as:

- Compressed Air Foam Systems (CAFS)
- Balanced pressure and in-line balanced pressure pumped proportioning equipment
- Balanced pressure bladder tank type proportioners
- Around-the-pump type proportioners
- Fixed or portable (in-line) venturi type proportioners
- Hand line nozzles with fixed induction/pickup tubes

The minimum and maximum usable temperatures for the ANSUL-A concentrate in this equipment is 30 °F (-1.1 °C) to 120 °F (49 °C).

Storage/Shelf Life

When stored in the packaging supplied (polyethylene drums or pails) or in equipment recommended by the manufacturer as part of the foam system and within the temperature limits specified, the shelf life of ANSUL-A Municipal "Class A" Fire Control Concentrate is about 20-25 years. The factors affecting shelf life and stability for ANSUL-A concentrate are discussed in detail in Johnson Controls Technical Bulletin No. 54. If the product is frozen during storage or transportation, thawing will return the product to a usable state. Mixing after thawing is desirable so as to assure a homogenous solution.

Compatibility

Refer to Johnson Controls Technical Bulletin No. 48 for a more detailed discussion of compatibility.

Different types of foam concentrates, for example AFFF and protein base should not be mixed under any circumstances.

Inspection

As with any fire suppression agent, ANSUL-A Municipal "Class A" Fire Control Concentrate should be inspected periodically, either in the concentrate or pre-mixed form. Please refer to the Field Inspection Manual (Part No. 31274) for detailed instructions on how to perform an inspection. An annual inspection is recommended unless unusual conditions of exposure occur, as described in Johnson Controls Technical Bulletin No. 54. In such cases, Johnson Controls recommendation should be sought.

Ordering Information

ANSUL-A Municipal "Class A" Fire Control Concentrate is available in pails, drums, totes or bulk shipment.

<u>Part No.</u>	<u>Description</u>	<u>Shipping Weight</u>
Pails		
433442	5 gal (19 L) 1.25 ft ³ (0.04 m ³)	45 lb (20.4 kg)
Drums		
433443	55 gal (208 L) 11.83 ft ³ (0.34 m ³)	495 lb (224.5 kg)
Totes		
433558	265 gal (1,003 L) 50.05 ft ³ (1.42 m ³)	2465 lb (1118 kg)

Bulk
433441*

*For bulk orders, consult an account representative.

Safety Data Sheets (SDS) are available at www.ansul.com

Note: The converted values in this document are provided for dimensional reference only and do not reflect an actual measurement.

ANSUL, ANSUL-A, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.