

Water Hand Portable Fire Extinguishers

Features

- Meets or exceeds UL and ULC requirements
- Simple operation and maintenance
- Trilingual glare-resistant, one-piece mylar nameplates (English, French, Spanish)
- Squeeze grip, positive on-off operation
- Stainless steel valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

Description

The SENTRY Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a stainless steel shell and stainless steel valve. The trilingual nameplate features easy to read step-by-step instructions for operating the extinguisher in English, French, and Spanish. The Schrader valve allows for easy recharge in the field. Use of fresh, clean water is recommended. Reference Manual Part No. 429442, latest revision.

Specifications

Model No.:	W02-1
UL/ULC Rating:	2-A
Capacity:	2.5 gal (9.5 L)
Extinguisher Height:	25.5 in. (648 mm)
Width:	9 in. (229 mm)
Depth:	7 in. (178 mm)
Range:	35 ft (10.7 m)
Discharge Time:	Approximately 50 seconds
Bracket:	Wall mount
Temperature:	+40 °F to 120 °F (4.5 °C to 48.9 °C)



006492

Ordering Information

Part No.	Description	Approximate Shipping Weight
430847	SENTRY Model W02-1 Pressurized Water-Type Fire Extinguisher 2.5 gal (9.5 L)	9.0 lb (4.1 kg)

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

SENTRY and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.