

## ANSUL® F-Class Model M6L Portable Fire Extinguisher

### Features

- Meets the requirements of EN3 and PED
- Simple operation and maintenance
- Rechargeable
- Easy-to-read pressure gauge
- Extended discharge range up to 5 m (16 ft)
- Swirl effect multi-purpose nozzle
- Steel cylinder finished in red, high-quality, polyester powder coating
- Corrosion resistant internal protective coating
- Suitable for use on live electrical equipment up to 1000VAC

### Description

The ANSUL® F-Class Model M6L is attractive and easy to use or maintain. The low pH fire extinguishing agent used in the extinguisher is a specially-formulated aqueous solution. It has been developed to provide rapid flame extinguishment and securement of hot fuels such as cooking shortenings.

### Applications

The ANSUL F-Class Model M6L liquid agent fire extinguisher is specifically designed for use on fires that involve combustible vegetable or animal fats in commercial cooking equipment. Typical appliances include fryers; griddles; range tops; upright, natural charcoal, or chain-type broilers; electric, lava rock, mesquite or gas-radiant char-broilers; and woks.

Newer, more efficient cooking appliances, plus the use of non-saturated cooking oils, require a fire extinguishing agent which will not only smother a fire but provide a cooling effect.

The extinguisher is ideally suitable for use in restaurants, hospitals, nursing homes, hotels, schools, airports, and other similar facilities.

It is used as a backup to an automatic fire suppression system. The energy source to the cooking equipment shall be shut off by the automatic system to help suppress the fire and permit the cooking media to cool below its auto-ignition temperature.

### Codes

- Pressure Equipment Directive (PED) – CE marked product
- European standard for portable extinguisher – EN3



008086

### Specifications

<b>Model</b>	M6L
<b>EN Rating</b>	13A, 75F
<b>Capacity</b>	6 L (1.6 gal)
<b>Height</b>	560 mm (22 in.)
<b>Width</b>	230 mm (9 in.)
<b>Range</b>	3 m to 5 m (9.8 ft to 16.4 ft)
<b>Discharge Time</b>	33 seconds
<b>Temperature Range</b>	0 °C to 60 °C (32 °F to 140 °F)

### Ordering Information

ANSUL F-Class Model M6L Liquid Agent Fire Extinguisher ordering information.

<u>Part No.</u>	<u>Description</u>
011 915	German Language
011 948	Czech Language
011 949	English Language
011 950	Spanish Language
011 951	French Language
300 415	Neufrol M (Wet chemical Agent) 6 L (1.6 gal)

**Note:** The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

ANSUL, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.