



## Power Generation

### CHALLENGE:

Protecting sub-stations, electrical switch rooms, control rooms, data communications and other critical areas

### SOLUTION:

ANSUL® FM-200™ Clean Agent Fire Suppression System

### APPLICATION:

Protecting critical operational infrastructure in cramped conditions

Power stations and power generation facilities incorporate a wide range of critical and ancillary services and buildings to ensure continued operations and plant uptime. Away from the primary power circuit, boiler and turbine system; vital facilities such as sub-stations, cable voids, control rooms, data communications and backup systems must be effectively protected against fire risk. Selecting the right solution to protect this critical plant infrastructure is key.

The ANSUL FM-200 Clean Agent Fire Suppression System has zero ozone depletion potential (ODP). The system uses FM-200 (HFC-227ea) fire extinguishant which vaporizes upon discharge and absorbs heat to rapidly suppress fire. This results in less damage to critical equipment, facilitating a much shorter recovery time and reducing downtime. Safe for use in occupied areas at the design concentration, the system helps protect critical infrastructure and delivers effective asset protection for power generation facilities.

The ANSUL FM-200 system is most effective when used with the automatic AUTOPULSE Detection and Control System to introduce the clean agent rapidly. This detection system is used to actuate a single, fixed fire suppression or alarm system based on inputs received from fire detection devices. The detection circuits can be configured using cross, counting, independent or priority-zone concepts.

Both automatic and manual actuators are available for release of the agent into the hazard area through fixed piping and nozzles. Seven nozzle sizes are available to provide the correct flow of agent in either 180 or 360 horizontal discharge patterns. For large hazards, cylinders can be connected to a common manifold.

The ANSUL FM-200 system carries UL, FM and ULC, as well as marine approvals. The system can be designed to meet the requirements of EN 15004, ISO 14520 and NFPA 2001 with components approved to provide the highest quality fire suppression system.