

## ANSULITE A111-FP18 1% $\times$ 1% Freeze-Protected AR-AFFF Concentrate

### Description

ANSULITE® A111-FP18 1x1 Freeze-Protected AR-AFFF (Alcohol Resistant Aqueous Film-Forming Foam) Concentrate combines fluoro- and hydrocarbon-surfactant technologies to provide superior fire and vapor suppression for Class B, polar solvent and hydrocarbon fuel fires. This synthetic foam concentrate is intended for forceful or gentle firefighting applications at 1% solution for hydrocarbon fuels and gentle firefighting applications at 1% solution for polar solvent fuels in fresh, salt, or hard water. A dual 1% solution level for ANSULITE® A111-FP18 1x1 minimizes the product required to protect against both hydrocarbon and polar solvent fire hazards.

ANSULITE® A111-FP18 1x1 foam solution utilizes three suppression mechanisms intended for rapid fire knockdown and superior burnback resistance:

- The foam blanket blocks oxygen supply to the fuel.
- Liquid drains from the foam blanket and forms either:
  - An aqueous film on a hydrocarbon fire, or
  - A polymeric membrane on a polar solvent fire which suppresses the vapor and seals the fuel surface.
- The water content of the foam solution produces a cooling effect for additional fire suppression.


#### TYPICAL PHYSIOCHEMICAL PROPERTIES AT 77 °F (25 °C)

Appearance	Pale yellow liquid
Density	1.09 ± 0.02 g/ml
pH	7.0 – 8.5
Refractive Index	1.3950 minimum
Viscosity*	50 cSt
Spreading Coefficient	3 dynes/cm minimum at 1% dilution
Pour Point	-22 °F (-30 °C)
Freeze Point	-26 °F (-32 °C)

\*Cannon-Fenske viscometer at 77 °F (25 °C)

Unlike most conventional pseudoplastic AR-AFFF products, ANSULITE® A111-FP18 1x1 Concentrate has Newtonian fluid properties similar to traditional AFFF concentrates.

The ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate formulation contains short-chain, C-6 fluorochemicals manufactured using a telomer-based process that does not produce PFOS.



009833

### Approvals, Listings, and Standards

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate is designed in accordance with National Fire Protection Association (NFPA) Standard 11 for Low-, Medium-, and High-Expansion Foam. The concentrate is approved, listed, qualified under, or meets the requirements of the following specifications and standards:

- UL Standard 162, Foam Liquid Concentrates
- ULC S564, Category 2, Foam Liquid Concentrates
- EN 1568:2008, Parts 3 and 4



### Application

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate is intended for use on both types of Class B fires: hydrocarbon fuels with low water solubility, such as crude oils, gasolines, diesel fuels, and aviation fuels; and polar solvent fuels with appreciable water solubility, such as methyl and ethyl alcohol, acetone, and methyl ethyl ketone. It may also be used in conjunction with dry chemical agents to provide even greater fire suppression performance.

ANSULITE® A111-FP18 1x1 Concentrate can be ideal for fixed, semi-fixed, and emergency response firefighting applications such as:

- Fuel or chemical storage tanks
- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Docks and on-board marine systems
- Mobile equipment
- Off-shore platforms
- Low-temperature operations

## Foaming Properties

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate may be effectively applied using most conventional foam discharge equipment at the correct dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

ANSULITE® A111-FP18 1x1 Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices. Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Aspirating low-expansion discharge devices typically produce expansion ratios from 3.5:1 to 10:1, depending on the type of device and the flow rate. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

### TYPICAL FOAM CHARACTERISTICS\* (Fresh and Salt Water)

Proportioning Rate	1%
Expansion Ratio	≥ 5
25% Drain Time (min:sec)	≥ 2:00
50% Drain Time (min:sec)	≥ 3:30

\*per EN 1568-3:2008 protocol

## Proportioning

The recommended operational temperature range for ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate is 0.5 °F to 120 °F (-17.8 °C to 49 °C) per UL-162. This foam concentrate can be correctly proportioned using most conventional, properly calibrated, in-line proportioning equipment, such as:

- Balanced and in-line balanced pressure pump proportioners
- Balanced pressure bladder tanks and ratio flow controllers
- Around-the-pump type proportioners
- Fixed or portable in-line venturi type proportioners
- Handline nozzles with fixed eductor/pick-up tubes

For immediate use: The concentrate may also be premixed with fresh or sea water to a 1% solution for hydrocarbon fuel fires or a 1% solution for polar solvent fuel fires.

For delayed use: Consult Technical Services for guidance regarding suitability of a stored pre-mix solution (fresh water only).

## Materials of Construction Compatibility

To help avoid corrosion, galvanized pipe and fittings should never be used in contact with undiluted ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate. Refer to Johnson Controls Technical Bulletin *Acceptable Materials of Construction* for recommendations and guidance regarding the compatibility of foam concentrate with common materials of construction in the firefighting foam industry.

## Storage and Handling

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate should be stored in the original supplied package (HDPE totes, drums, or pails) or in the recommended foam system equipment as outlined in Johnson Controls Technical Bulletin *Storage of Foam Concentrates*. A thin layer up to 1/4 in. (6 mm) thick of appropriate-grade mineral oil may be applied to the surface of the foam concentrate stored in a fixed, atmospheric storage container to help minimize evaporation. Consult Johnson Controls for further guidance regarding the use of mineral oil to help seal the surface of AR-AFFF concentrates.

The concentrate should be maintained within the recommended operational temperature range. Freezing of the product should be avoided. If, however, the product freezes during transport or storage, it must be thawed and inspected for signs of separation. If separation has occurred, or is suspected, the ANSULITE® A111-FP18 1x1 Concentrate should be mechanically mixed until homogeneous, and additional testing may be required after mixing to verify the product quality.

Factors affecting the foam concentrate's long-term effectiveness include temperature exposure and cycling, storage container characteristics, air exposure, evaporation, dilution, and contamination. The effective life of ANSULITE® A111-FP18 1x1 Concentrate can be maximized through optimal storage conditions and proper handling. ANSULITE® foam concentrates have demonstrated effective firefighting performance with contents stored in the original package under proper conditions for more than 10 years.

Mixing ANSULITE® A111-FP18 1x1 Concentrate with other foam concentrates for long-term storage is not recommended. Use in conjunction with comparable 1x1 AR-AFFF products for immediate incident response is appropriate.

## Inspection

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate should be inspected periodically in accordance with NFPA 11, EN 13565-2, or other relevant standard. A representative concentrate sample should be sent to Johnson Controls Foam Analytical Services or other qualified laboratory for quality analysis per the applicable standard. An annual inspection and sample analysis is typically sufficient unless the product has been exposed to unusual conditions.

## Ordering Information

ANSULITE® A111-FP18 1x1 AR-AFFF Concentrate is available in pails, drums, totes, or bulk shipment.

Part No.	Description	Approximate Shipping Weight
<b>Pails</b>		
443146	5 gal (19 L)	45 lb (20.4 kg)
443146E	5 gal (19 L)	45 lb (20.4 kg)
<b>Drums</b>		
443147	55 gal (208 L)	495 lb (224.5 kg)
443147E	55 gal (208 L)	495 lb (224.5 kg)
<b>Totes*</b>		
443148	265 gal (1,003 L)	2,463 lb (1,117 kg)
443148E	265 gal (1,003 L)	2,463 lb (1,117 kg)

For bulk orders, consult an account representative.

\*Totes are not UL/ULC approved packaging.

Safety Data Sheets (SDS) are available at [www.ansul.com](http://www.ansul.com).

If any foam product is discharged into the environment, efforts should be made to control, contain and collect the discharge for proper disposal, while following all applicable laws, regulations, and codes. Further information regarding the use, discharge, and disposal of firefighting foams can be found at [www.ansul.com](http://www.ansul.com).

**Note:** The converted values in this document are provided for dimensional reference only and do not reflect an actual measurement.

ANSUL®, ANSULITE®, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.